

MILLAT

HYDRAULIC TIPPING TRAILER

SPECIFICATIONS:

Description	Spec. B	Spec. C
Type	Hyd. Tipping	Hyd. Tipping
Capacity	5-Ton	8-10 Ton
Vessel Size	11' x 6.5' x 2'	12' x 7' x 2.5'
Floor	MS Sheet SWG 10	
Side Wall	MS Sheet SWG 12	
Chassis Frame		
Lower Channel:	8' x 3'	10' x 3'
Upper Channel:	6' x 3'	6' x 3'
Axle Size		
Length:	52"	56"
Outer Dia:	5.5"	6"
Wall Thickness:	3/8"	3/8"
Rims		
Qty:	2	4
Size:	9.00-20	9.00-20
Tipping Device:	Double acting heavy duty locally made Ram with mechanical linkage.	
Tipping Angle:	55 Degrees.	
Maximum Lift Time:	10 Seconds at 1500 - 1789 rpm of Tractor Engine to its full height in empty Condition.	
Hydraulic Kit For Trolley:		
Spool Valve:	Imported Minimum Rod Dia, 20mm	
Selector Valve:	Imported Minimum Rod Dia. 20mm.	
Hyd. Hoses:	Imported from above countries, the Crimping and Hoses should bear a pressure of 4000 psi. There should be no joint between two connections.	
Quick Attachment Coupler Set:	Imported.	