

## 7 Snow Blower



### SPECIFICATIONS

Width (mm)	650 lbs
Cutting Width	60 -96"
Cutting Height	25"
Depth	38"
Height	57"
Flow Rates	12-45 GPM
Throw Distance	45 - 70 Ft
Blower Diameter	18"
Hydraulic Blower	Two-Stage

## 8 Tree Puller

### SPECIFICATIONS

Weight	415 Pounds
Jaw Opening	11", Rows of Serrated Teeth=4"
Steel Surcharge	Yes



## 9 Trencher



### SPECIFICATIONS

Weight	700 lbs
Flow Rating	14-23 GPM
Auger Discharge	18"
Chain Width	6"
Tooth Specifications	Shark style 70/30 Tungsten /Dirt Teeth Ratio
Drive System	Planetary Gear Drive
Steel Surcharge	yes

## 10 Pallet Forks

### SPECIFICATIONS

Weight	400 lbs
Width	48"
Fork Frame Height	37"
Rating	4400 lbs
Material	Steel
Elongation	12%
Surface Hardness	255-385HB
Tensile Strength	935 MPANMM



## 11 Grader



### SPECIFICATIONS

Width	72"
Depth	48" Plus Mount
Height	18"
Weight	1000 lbs
Tubing	3" x 4" x .38" Mill Structural Tubing
Plate Steel Side	1/4" A50 Structural Plate
Wear Surface	1/2" x 2" AR400
Blades	High-carbon Manganese Steel Alloy Rc 28

## 12 Plate Compactor

### SPECIFICATIONS

Weight	525 lbs
Impulse Force	3400 lbs
Plate Width	17.4
Plate Length	20
Direction of Travel	Forward or Reverse
Material	High Alloy Strength Steel
Frequency	2000 VPM



## 13 Post Puller



### SPECIFICATIONS

Weight	280 lbs
Max Opening	12
Cylinder	2" Bore with 3" Stroke
Teeth Closure	Gap to Tip, Solid Piece When Closed
Teeth Height from Tip to Base	4"
Teeth Thickness	1/2"

And Many More!



**MILLAT TRACTORS LIMITED**  
9-km, Shiekhpura Road, Shahdara, Lahore-Pakistan.  
infor@millat.com.pk | ipd@millat.com.pk

Lahore  
Ph: 3791021-25  
UAN: 111-200-786 Fax: 37925835

Karachi  
Ph: 334553782  
UAN: 111-200-786 Fax: 345566321

Islamabad  
Ph: 2271470  
UAN: 111-200-786 Fax: 32270693

Multan  
Ph: 6537371

Sialkot  
Ph: 5815041 Fax: 5815042



# MILLAT SKID STEER TRUCK

Model: **MCTH 730**



with **MANY** Dynamic Attachments

## "YOUR MOST RELIABLE PARTNER"

FOR



Housing



Municipality



Construction



Industrial



Town Development



Snow Removal

## 1 Front Loader



### GENERAL

Model		MCAT
Rated Capacity	kg	730
Rated Flow	L/min	80
Discharge Height	mm	2266
Discharge Distance	mm	662
Power Type		Diesel
Control Type		Manual Control

### PERFORMANCE

Max. Speed	km/h	11-12
Tipping Load	kg	1460
Lifting Type		Radius
Bucket Capacity	M <sup>3</sup>	0.47
Total Weight With Bucket	kg	2842
Total Weight Without Bucket	kg	2628

### ENGINE

Model		Millat D3.1524
Rated Horsepower / Rpm	ps	50 / 2250
Rated Torque / Rpm	Nm	172 / 1350
Number Of Cylinders		3
Displacement	L	2.5
Fuel Tank Capacity	L	79
Pneumatic (Tubeless Tires)		10-16.5

### DIMENSIONS

Overall Length With Bucket	mm	3348
Overall Length Without Bucket	mm	2522
Overall Width With Bucket	mm	1800
Overall Width Without Bucket	mm	1730
Overall Height	mm	2070
Max. Operating Height	mm	3910
Front Turning Radius	mm	2027
Front Turning Radius Without Attachments	mm	1380
Rear Turning Radius	mm	1527
Wheel Base	mm	991
Tread	mm	1465

### TYRE

Pneumatic (Tubeless Tires)		10-16.5
----------------------------	--	---------

### Main Characteristics

- American Danfoss Pump
- France Poclain Hydraulic Motor With Parking Brake
- Tubeless Tire 10-16.5
- Hydraulic Balance
- Manual Control
- Open Cab With Fan
- Warning Light
- Reverse Buzzer
- Mirror Outside Cab
- Front & Rear Turning Light
- Rear Width Light
- Rated Capacity 730kg
- Dump Height 2.27m
- Bucket & Arm Safety Lock

## 2 4 in 1 Multi-Purpose Loader



Step:1  
Collect

### SPECIFICATIONS

Width (mm)	1889
Height (mm)	768
Length (mm)	879
Open Distance (mm)	718
Pressure (Mpa)	20
Clamping Force (N)	8230
Weight (Kg)	460
Capacity (m <sup>3</sup> )	0.48

Step:2  
Lift



Step: 3 & 4  
Discharge & Grab



## 3 Hydraulic Hammer



### SPECIFICATIONS

Weight (kg)	260
Length (mm)	1160
Pressure (Bar)	80-100
Flow Range (L/min)	20-35
Frequency (Bpm)	650-1200
Rod Dia. (Mm)	45
Energy (J)	225

## 4 Front Blade



### SPECIFICATIONS

Length (mm)	1207
Width (mm)	2130
Height (mm)	580
Max. Turn Angle	30°
Work Width(mm)	1845
Turn 30°	

## 5 Backhoe Arm



### SPECIFICATIONS

Length (mm)	1869
Width (mm)	1320
Height (mm)	776
Weight (kg)	425
Capacity (m <sup>3</sup> )	0.06

## 6 Vibratory Roller



### SPECIFICATIONS

Width (mm)	1830
Drum width(mm)	1677
Height (mm)	788
Length (mm)	990
Drum Dia.(mm)	609
Weight (Kg)	976
Vibration(Kn)	35
Speed (vpm)	2600
Tilt Angle (°)	15