



MILLAT'S

MF 260 2WD (60 HP)

A Multi-Purpose Tractor

- High performance, Fuel Efficient, Diesel Turbocharged Engine
- Less Smoke Emission due to
- Better Fuel Burning
- Oil Cooler Added for Effective Cooling
- High PTO Power for Efficient Operation of Tube wells, Rotavators, Threshers etc.
- Spring Suspension Deluxe Seat.
- Efficient Oil Immersed Multi-Disc Brakes
- Robust Straddle Rear Axle.
- Rear View Mirror
- Magnetic Drain Plug
- Mobile Charging Port
- Maintenance Free Battery
- Wider Heat Shield.



Radiator Bottle and Coolant



New Hand Throttle Lever



Heavy Duty Top Link



Modern Tappet Cover



Heavy Duty Yoke Tubes



Single Earth Wiring



The Heartbeat of the Farmers...

MILLAT TRACTORS LIMITED

For further info:
You Millat Tractors Limited Official
Millat Tractors Limited
www.millat.com.pk

MILLAT'S

MF 260 Specifications

PERFORMANCE

Engine power at 2250 rpm	60 (B.S.) hp*
Torque at 1600 engine rpm	212 Nm
PTO power at rated engine speed	48.0 hp**

*Certified to BS AU 141a: (1971)

**Manufacturer's estimate

ENGINE

Type	Diesel T3.1524
No. of cylinders	3
Injection	Direct
Bore	91.5 mm
Stroke	127 mm
Capacity (litres)	2.5 l
Aspiration	Turbo
Compression ratio	15.5:1
Starting aid	Thermostat
Throttle control	Hand and foot
Cooling	Water
Air cleaner type	Oil bath
Air pre cleaner	Over bonnet, air swirl
Fuel filter	Dual, high capacity
Exhaust	Vertical muffler
Oil Cooler	Air Cooled, Fin Type
Oil drain plug	Magnetic

ELECTRICS

Voltage	12 V, Negative earth
Battery	88 Ah (Maintenance free)
Alternator/Starter Motor	34A / 1.8 KW

CLUTCH

Type	Dual
Diameter	305X254 mm

TRANSMISSION

Type	Sliding spur
Number of gears	8 forward, 2 reverse
Road speed at 2250 engine rpm with 14.9/13-28 tyres	
Gear	Speed (Km/hr)
Forward 1 (First low)	2.6
Forward 2	3.8
Forward 3	5.2
Forward 4	7.0
Forward 5 (First high)	10.4
Forward 6	15.2
Forward 7	20.8
Forward 8	27.9
Reverse 1 (Low)	3.5
Reverse 2 (High)	14.1

POWER TAKE OFF

Type	Live
Engine speed at 540 PTO rpm	1,789 rpm
Shaft diameter	35 mm
No. of splines	6

HYDRAULICS

Functions	Draft control, Position control, Response control, Constant pumping
Pump type	Reciprocating pump Ferguson Pump
Oil flow	16.7 l/min
Pressure	21.2 MPa at normal operating temp.
Lift capacity at lower links end with lower links horizontal	2,145 Kg
Lower links	With Cat I & CAT II interchangeable balls Adjustable Heavy Duty Yoke Tubes

STEERING

Type	Manual
FRONT AXLE	
Type	Box Section, adjustable

REAR AXLE & BRAKES

Axle type	Straddle with epicyclic reduction unit
Brake type	Oil immersed, multi-disc
Brakes actuation	Mechanical
Parking brake	Hand lever operated

INSTRUMENTATION

Gauges	Tachometer, Hourmeter Fuel level, Water temp. & Battery condition
Warning lights	Direction indicator Electric charge Head light main beam Low engine oil pressure indication light

TYRES

Front	7.50-16
Rear	14.9/13-28

TRACK ADJUSTMENT

Front axle	1,390-2,170 mm
Rear axle	1776-2200 mm

WEIGHT AND DIMENSIONS (APPROX)

(With 7.50-16 Front & 14.9/13-28 rear wheel with full fuel, oil and water)

Weight	
Gross Weight	1,925 kg
Dimensions	
Overall length	3,252 mm
Overall width	1,872 mm
Wheel base	1,884 mm

Height	
Over exhaust	2,210 mm
Over steering wheel	1,455 mm
Turning Circle	
Without brakes	7,370 mm
Ground Clearance	
Under engine sump	410 mm

CAPACITIES

Fuel tank	50 l
Engine sump	6.8 l
Cooling system	12.5 l
Hydraulic system	38.0 l
Oil bath air cleaner	0.75 l
Steering box	0.75 l

STANDARD EQUIPMENT

Weight frame, Standard tool box with set of tools, Top link, USB port, Top link end Cat-I & II balls, Check chains, Spring suspension seat, Flat top fenders, Rear view mirror, Operator's and service manual, Wider heat shield.

OPTIONAL EQUIPMENT

Swinging drawbar, Front weights, Pintle Hook

and 9 Hole drawbar.

OPERATOR AREA

Seat	Cushioned
Fenders	Flat top
Tool	Standard

Note:

Millat Tractors Ltd. reserve the right to change specifications without prior notice.



The Heartbeat of the Farmers...

MILLAT TRACTORS LIMITED

9-km. Sheikhpura Road, Shahdara, Lahore-Pakistan
info@millat.com.pk www.millat.com.pk

	LAHORE	KARACHI	ISLAMABAD	MULTAN	SUKKUR
Phone ➤	042-37911021-25 042-37925835 042-37924166	021-34553752 021-34556321	051-2271470 051-2270693	061-6537371 061-6539271	071-5815041 071-5815042
UAN ➤	111-200-786	111-200-786	111-200-786		