



MILLAT'S

MF 260 Deluxe (60 HP)

A UPGRADED, EFFICIENT, COMFORTABLE & MULTIPURPOSE TRACTOR

- Hydrostatic Power Steering
- Heavy Duty Front Axle and Spindles
- Heavy Duty Front Tyres (12 PR)
- Heavy Duty Rear Tyres (8-PR)
- Extended Tractor Length/Wheel Base
- Spacious Operator Area with Transmission Cover
- Magnetic Drain Plug
- Sun Canopy
- Rear View Mirror
- Mobile Charging Port
- Heat Shield
- Maintenance Free Battery
- Additional Fuel Filtration System



Radiator Bottle and Coolant



New Hand Throttle Lever



Heavy Duty Top Link



Modern Tappet Cover



Heavy Duty Yoke Tubes



Single Earth Wiring



The Heartbeat of the Farmers...

MILLAT TRACTORS LIMITED

For further info:
You  Millat Tractors Limited Official
 Millat Tractors Limited
 www.millat.com.pk

MILLAT'S

MF 260 Deluxe Specifications

PERFORMANCE

Engine power at 2250 rpm 60 (B.S.) hp*
 Torque at 1600 engine rpm 212 Nm
 PTO power at rated engine speed 48.0 hp**
 *Certified to BS AU 141a: (1971)
 **Manufacturer's estimate

ENGINE

Type Diesel T3.1524
 No. of cylinders 3
 Injection Direct
 Bore 91.5 mm
 Stroke 127 mm
 Capacity (litres) 2.5 l
 Aspiration Turbo
 Compression ratio 15.5:1
 Starting aid Thermostat
 Throttle control Hand and foot
 Cooling Water
 Air cleaner type Oil bath
 Air pre cleaner Over bonnet, air swirl
 Fuel filter Dual, high capacity
 Exhaust Vertical muffler
 Oil Cooler Water Cooled

ELECTRICS

Voltage 12 V, Negative earth
 Battery 88 Ah (Maintenance free)
 Alternator/Starter Motor 34A / 1.8 KW

CLUTCH

Type Dual
 Diameter 305X254 mm

TRANSMISSION

Type Sliding spur
 Number of gears 8 forward, 2 reverse
 Road speed at 2250 engine rpm with

14.9/13-28 tyres
 Gear Speed (Km/hr)
 Forward 1 (First low) 2.6
 Forward 2 3.8
 Forward 3 5.2
 Forward 4 7.0
 Forward 5 (First high) 10.4
 Forward 6 15.2
 Forward 7 20.8
 Forward 8 27.9
 Reverse 1 (Low) 3.5
 Reverse 2 (High) 14.1

POWER TAKE OFF

Type Live
 Engine speed at 540 PTO rpm 1,789 rpm
 Shaft diameter 35 mm
 No. of splines 6

HYDRAULICS

Functions Draft control,
 Position control,
 Response control,
 Constant pumping
 Pump type Reciprocating pump
 Ferguson Pump
 Oil flow 16.7 l/min
 Pressure 21.2 MPa at normal
 operating temp.
 Lift capacity at lower links
 end with lower links
 horizontal 2,145 Kg
 Lower links With Cat I & CAT II
 interchangeable balls
 Adjustable Heavy Duty Yoke
 Tubes

STEERING

Type Hydrostatic

FRONT AXLE

Type Box Section, adjustable

REAR AXLE & BRAKES

Axle type Straddle with epicyclic
 reduction unit
 Brake type Oil immersed, multi-disc
 Brakes actuation Mechanical
 Parking brake Hand lever operated

INSTRUMENTATION

Gauges Tachometer, Hourmeter
 Fuel level, Water temp. &
 Battery condition
 Warning lights Direction indicator
 Electric charge
 Head light main beam
 Low engine oil pressure
 indication light

TYRES

Front 7.50-16
 Rear 14.9/13-28

TRACK ADJUSTMENT

Front axle 1470-2100 mm
 Rear axle 1776-2200 mm

WEIGHT AND DIMENSIONS (APPROX)

(With 7.50-16 Front & 14.9/13-28 rear
 wheel with full fuel, oil and water)

Weight
 Gross Weight 2100
Dimensions
 Overall length 3450 mm
 Overall width 1872 mm
 Wheel base 2230 mm
Height
 Over exhaust 2290 mm
 Over steering wheel 1540 mm
 Turning Circle
 Without brakes 8760 mm
 Ground Clearance
 Under engine sump 450 mm

CAPACITIES

Fuel tank 50 l
 Engine sump 6.8 l
 Cooling capacity 12.5 l
 Hydraulic system 42.0 l
 Oil bath air cleaner 0.75 l
 Steering Pump 2 l

STANDARD EQUIPMENT

Weight frame, Sun Canopy
 Standard tool box with set of tools, Top link, USB port
 Top link end Cat-I & II balls, Check chains, Spring
 suspension seat, Flat top fenders, Rear view mirror,
 Operator's and service manual, Wider heat shield

OPTIONAL EQUIPMENT

Swinging drawbar, Front weights, Pintle Hook and 9
 Hole drawbar.

OPERATOR AREA

Seat Cushioned
 Fenders Flat top
 Tool Standard

Note:

Millat Tractors Ltd. reserve the right to change
 specifications without prior notice.



The Heartbeat of the Farmers...

MILLAT TRACTORS LIMITED

9-km. Sheikhpura Road, Shahdara, Lahore-Pakistan
 info@millat.com.pk www.millat.com.pk

	LAHORE	KARACHI	ISLAMABAD	MULTAN	SUKKUR
Phone	042-37911021-25	021-34553752	051-2271470	061-6537371	071-5815041
	042-37925835	021-34556321	051-2270693	061-6539271	071-5815042
	042-37924166				
UAN	111-200-786	111-200-786	111-200-786		